

RISK MANAGEMENT MEASURES CAS 1066-35-9 Chlorodimethylsilane

Chemical safety assessments have been performed to assess the risk associated with the following uses :

Identified use	Sector of Use - main user groups (SU)	Sector of Use – sectors of end-use	Preparation Category (PC)	Process category (PROC)	Article category (AC)	Environmental Release Category (ERC)
Chain terminator in polymerization reactions	SU3	SU8, 9	PC19	PROC1, PROC2, PROC3, PROC8b, PROC9	N/A	ERC 6c
Intermediate	SU3	SU8, 9	PC19	PROC1, PROC2, PROC3, PROC8b, PROC9	N/A	ERC6a
Semiconductor manufacture	SU3	SU16	PC33	PROC1, 8b	N/A	ERC6b
Laboratory chemical	SU3, SU22	SU24	PC21	PROC15	N/A	N/A

General provisions

Safe use has been demonstrated by calculation of risk characterisation ratios. These are based on the following risk management measures:

Exposure scenario	Description	General measures	Specific Human Health risk management measures	Specific Environment risk management measures
ES1	Production (site specific)	(i) Rigorous containment and safe handling in line with industry best practice. (ii) Procedural and technological control using Best Available Technique (BAT)	(i) Local Exhaust ventilation (LEV) (ii) Personal Protective Equipment (PPE): Gloves/ gauntlets (5-layer laminate of PE and EVOH (4H) or Butyl & Viton types recommended); Full-face respirator with ABEK-filter; Goggles or face shield; and Self-contained, positive pressure breathing apparatus (for prolonged or high exposures) (iii) Specific workers' training (iv) Duration of exposure: <15 min for PROC8b and 9	(i) Use of air emission abatement equipment such as incinerators and scrubbers (ii) Treatment of effluent in biological waste water treatment plant. (iii) Incineration of waste
ES2, ES3 and ES4	Monomer, Chemical intermediate and use in manufacture of	Rigorous containment and safe handling in line with industry best practice.	(i) Local Exhaust ventilation (LEV) (ii) Personal Protective Equipment (PPE): Gloves/ gauntlets (5-layer laminate of	(i) Use of air emission abatement equipment such as incinerators, scrubbers and fabric filters is applicable as a

	semiconductors (Down stream user)		PE and EVOH (4H) or Butyl & Viton types recommended); Full-face respirator with ABEK-filter; Goggles or face shield and Self-contained, positive pressure breathing apparatus (for prolong or high exposures) (iii) Specific workers' training (iv) Duration of exposure: <15 min for PROC2, 3, 8b and 9	'best practice'. (ii) Treatment of effluent in waste water treatment plant.
ES5	Laboratory reagent	Good Laboratory Practice (GLP)	(i) Local Exhaust ventilation (Fume cupboard) (ii) Personal Protective Equipment (PPE): Gloves/ gauntlets (5-layer laminate of PE and EVOH (4H) or Butyl & Viton types recommended) (iii) Basic workers' training (iv) Duration of exposure: 15 min to 1 h	N/A